

FBE60 Series (Φ60mm)

MOTOR FEATURE:

- RATED OUTPUT POWER : 5~25W
- RATED VOLTAGE : 12~48VDC
- OPERATIONAL SPEED :2900~ 4000RPM
- MAX. OUTPUT POWER : 75W
- Sleeve/Steel Ball bearing for option
- Replaceable Brush Type for option
- Pinion shaft or other requirement for option



Dimensions

(UNIT:mm)

--	--

Typical Specifications (F =ferrite magnet, N= rare earth magnet)

MODEL	Rated						Weight (kg)	Length L (mm)
	Voltage (V)	Output (W)	Current (A)	Speed (RPM)	Torque (kgf-cm)	Rating		
FBE60-N012006-H**	12	6	0.19	3200	0.18	cont	0.5	32
FBE60-N012005-M**	12	5	0.14	2900	0.17	cont	0.5	32
FBE60-N024006-H**	24	6	0.09	3200	0.18	cont	0.5	32
FBE60-N024005-M**	24	6	0.08	2900	0.20	cont	0.5	32
FBE60-N048005-H**	48	5	0.05	3200	0.15	cont	0.5	32
FBE60-N048004-M**	48	5	0.04	2900	0.17	cont	0.5	32
FBE60-N012007-H**	12	7	0.28	4000	0.17	cont	0.6	42
FBE60-N012007-M**	12	7	0.21	3000	0.23	cont	0.6	42
FBE60-N024010-H**	24	10	0.14	4000	0.24	cont	0.6	42
FBE60-N024010-M**	24	10	0.11	3100	0.31	cont	0.6	42
FBE60-N048022-H**	48	22	0.07	4000	0.54	cont	0.6	42
FBE60-N048022-M**	48	22	0.05	3100	0.69	cont	0.6	42

- ** = "WB" for wire lead type Ball bearing, or "TB" for terminal type Ball bearing
- Sinwan reserves the right to change data and improve electrical & mechanical design without notice

- Pls discuss with us when you place an order non-standardized products such as voltage, speed and others.
- Mass production by standardizing the various types and manufacture the products with special size by order.
- Design or Motor spec. can be changed for quality improvement without any notice.